

Withstanding Voltage: 20 kV/mm, UL224, AC2500V, 1min  
 Temperature Resistance: -55°C up to +135°C  
 Shrink Temperature: min. 90°C  
 Specifications: UL 224, 125°C; CSA 22.2  
 Rate of shrinking: 3:1


Order Code	ØID1 min. (mm)	ØID2 internal (mm)	t max. after shrinking (mm)	Packaging Unit (m/Reel)
71201615	1,5	0,5	0,45	150
71203215	3,0	1,0	0,55	150
71206415	6,0	2,0	0,65	75
71209515	9,0	3,0	0,75	75
71212715	12,0	4,0	0,75	50
71219115	18,0	6,0	0,85	30
71225415	24,0	8,0	1,00	30
71239015	39,0	13,0	1,15	30

Würth Elektronik eiSos GmbH & Co. KG  
 EMC & Inductive Solutions

Max-Eyth-Str. 1  
 74638 Waldenburg  
 Germany  
 com. +49 79 42 945 - 0

www.we-online.de  
 eiSos@we-online.de



CREATED DaF	CHECKED SKI	GENERAL TOLERANCE DIN ISO 2768-1m	PROJECTION METHOD 	SCALE 3 : 1
DESCRIPTION <b>AShST Heat Shrinking Tubes</b>		MATERIAL Polyolefin, black		
ORDER CODE 712 xxx 15				
SIZE Type X385	WEIGHT xxx	STATUS Released	DATE 2015-08-17	BUSINESS UNIT eiCan
				PAGE 1 / 1

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Würth Elektronik eiSos GmbH & Co KG products are neither designed nor intended for use in areas such as military, aerospace, aviation, nuclear control, submarine, transportation (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc.. Würth Elektronik eiSos GmbH & Co KG must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.