



Order Code	ØID1 min. (mm)	ØID2 internal (mm)	t max. after shrinking (mm)	Packaging Unit (m/Reel)
71201612	1,6	0,8	0,45	150
71202412	2,4	1,2	0,50	150
71203212	3,2	1,6	0,50	150
71204812	4,8	2,4	0,50	75
71206412	6,4	3,2	0,65	75
71209512	9,5	4,8	0,65	75
71212712	12,7	6,4	0,65	50
71216012	16,0	8,0	0,65	50
71219012	19,0	9,5	0,76	30
71225412	25,4	12,7	0,89	30
71232012	32,0	16,0	0,89	30
71238112	38,1	19,0	1,02	30

Withstanding Voltage: 20 kV/mm, UL224,AC2500V,1min
 Temperature Resistance: -55°C up to +135°C
 Shrink Temperature: min. 90°C
 Specifications: UL 224, 125°C; CSA 22.2
 Rate of shrinking: 2:1

Würth Elektronik eiSos GmbH & Co. KG
 EMC & Inductive Solutions

Max-Eyth-Str. 1
 74638 Waldenburg
 Germany
 com. +49 79 42 945 - 0

www.we-online.de
 eiSos@we-online.de



CREATED DaF	CHECKED SKI	GENERAL TOLERANCE DIN ISO 2768-1m	PROJECTION METHOD		SCALE 3 : 1
DESCRIPTION AShST Heat Shrinking Tubes			MATERIAL Polyolefin, black		
ORDER CODE 712 xxx 12					
SIZE Type N100	WEIGHT xxx	STATUS Released	DATE 2015-08-17	BUSINESS UNIT eiCan	PAGE 1 / 1

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Würth Elektronik eiSos GmbH & Co KG products are neither designed nor intended for use in areas such as military, aerospace, aviation, nuclear control, submarine, transportation (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc.. Würth Elektronik eiSos GmbH & Co KG must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.